

ASROCK 775i65GV Socket 775 Motherboard [ASROCK 775i6]

MYR128.00



General

CPU - LGA775 for Intel? Pentium 4/Celeron processor

- Support Intel? Dual Core Processors*, including Pentium D and Extreme Edition
- FSB 800/533/400 MHz
- Supports Hyper-Threading Technology
- Prescott support
- Intel? 04B/04A processors compatible

*Only supported with PCB version R1.04 or higher, and BIOS version P1.90 or higher.

Chipset - Northbridge: Intel? 865GV

- Southbridge: Intel? ICH5

Memory - Dual Channel DDR memory technology

- Supports DDR400/333/266 non-ECC, un-buffered memory
- DIMM slots: 2

- Max. capacity of system memory: 2GB

BIOS - 2Mb AMI BIOS with ACPI, SM BIOS 3.0, PnP

Audio, Video and Networking

Graphics - Integrated Intel? Extreme Graphics 2 in Intel? 865GV chipset

Audio - CMedia CMI9739A 6 channel AC'97 audio codec

LAN - Realtek RTL8101 PCI 10/100 Fast Ethernet controller

- 802.3u, WOL supported

Expansion / Connectivity

Slots - Worldwide patent ASRock A.G.I.8X graphics upgrade slot (AGP8X/4X compatible)

- 3 x PCI slots(PCI 2.2 compliance)

- 1 x AMR slot

Connector - 2 x SATA 1.5Gb/s connectors

- 2 x ATA100/66 IDE connectors (supports 4 x IDE devices)

- 1 x Floppy connector

- CPU/Chassis FAN connectors
- 20 pin ATX power connector
- 4 pin +12V power connector
- IDE LED connector
- CD/AUX audio in header
- Front panel audio connector
- 2 x USB 2.0 port pin headers
- 1 x COM port header

Rear Panel I/O ASRock I/O Plus

- 6 x USB2.0 ports
- 1 x RJ45 LAN port
- 1 x VGA port
- 1 x PS2 Keyboard connector
- 1 x PS2 Mouse connectors
- 1 x Parallel port (LPT1)
- 1 x Audio ports (Line In/Out, Mic In)

Other Features / Miscellaneous

Hybrid Booster - CPU Frequency Stepless control

- ASRock U-COP
- Boot Failure Guard (B.F.G)

Support CD - Drivers, Utilities, Anti Virus Software, ASRock PC DIY Demo, ASRock LGA775 CPU Installation Live Demo

Accessories - Quick Installation Guide, Support CD, I/O shield

- Floppy/ATA 100 Cables
- 1 x SATA Data Cable (optional)
- 1 x SATA 1-to-1 Power Cable (optional)

Form Factor - Micro ATX, 244mm x 218mm

OS - Microsoft? Windows? 98SE / ME / 2000 / XP compliant

Certifications - FCC, CE, MS WHQL

[Vendor Information](#)

Customer Reviews: There are yet no reviews for this product.
Please log in to write a review.